



Perfect packaging solution starts here

完美包装方案，从此开始

盒式真空空气调包装机 HVT SERIES

TRAY VACUUM GAS FLUSHING PACKAGING MACHINE



HVT-450M



HVT-450A

| Parameters | HVT-350M | HVT-450M | HVT-550M |
|--|--|-------------------|-------------------|
| 电源电压(V/Hz) Voltage | 三相 (3PH) AC 380/50 220/60 | | |
| 热封功率(W) Sealing Power | 2000 | 2000 | 2000 |
| 气源气压(MPa) Gas Power | 0.5-0.6 | 0.5-0.6 | 0.5-0.6 |
| 冷却方式 Cooling Type | 水冷 Water-cooling | | |
| 包装能力(times/min) Capacity | 仅热封10-12次/分钟; 真空、充气+热封3-5次/分钟; Only sealing 10-12 times/min. Vacuum, gas flushing+sealing 3-5 cycles/min. | | |
| 充气气体 Gas flushing | N ₂ or N ₂ + CO ₂ | | |
| 工作室尺寸(L×W)(mm) Chamber Dimensions | 350 × (100-400) | 450 × (200-400) | 550 × (200-600) |
| 外形尺寸(L×W×H)(mm) External Dimensions | 1360 × 740 × 1530 | 1360 × 840 × 1530 | 1360 × 940 × 1530 |
| 净重(kg) Net Weight | 约(Approx.)600 | 约(Approx.)670 | 约(Approx.)750 |
| 真空泵排气量 (m ³ /h) Pump capacity | 63 | 63 | 63 |

| Parameters | HVT-350A | HVT-450A | HVT-550A |
|--|--|--------------------|--------------------|
| 电源电压(V/Hz) Voltage | 三相 (3PH) AC 380/50 220/60 | | |
| 热封功率(W) Sealing Power | 2000 | 2000 | 2000 |
| 气源气压(MPa) Gas Power | 0.5-0.6 | 0.5-0.6 | 0.5-0.6 |
| 冷却方式 Cooling Type | 水冷 Water-cooling | | |
| 包装能力(times/min) Capacity | 仅热封10-12次/分钟; 真空、充气+热封3-5次/分钟; Only sealing 10-12 times/min. Vacuum, gas flushing+sealing 3-5 cycles/min. | | |
| 充气气体 Gas flushing | N ₂ or N ₂ + CO ₂ | | |
| 工作室尺寸(L×W)(mm) Chamber Dimensions | 350 × (100-400) | 450 × (200-400) | 550 × (200-600) |
| 外形尺寸(L×W×H)(mm) External Dimensions | 2950 × 940 × 1700 | 2950 × 1040 × 1700 | 2950 × 1140 × 1700 |
| 净重(kg) Net Weight | 约(Approx.)600 | 约(Approx.)670 | 约(Approx.)750 |
| 真空泵排气量 (m ³ /h) Pump capacity | 63 | 63 | 63 |

注: 可选配贴体包装功能。

Note: Skin pack function is optional.